

De perete — seria CHV-5SW

10 modele: CHV-5SW15NK2 ... CHV-5SW71NK2

| Model                          | 5SW15NK2    | 5SW18NK2    | 5SW22NK2    | 5SW28NK2    | 5SW36NK2     | 5SW45NK2     | 5SW50NK2     | 5SW56NK2     | 5SW63NK2     | 5SW71NK2     |
|--------------------------------|-------------|-------------|-------------|-------------|--------------|--------------|--------------|--------------|--------------|--------------|
| Capacitate de răcire (kW)      | 1.5         | 1.8         | 2.2         | 2.8         | 3.6          | 4.5          | 5            | 5.6          | 6.3          | 7.1          |
| Capacitate de încălzire (kW)   | 1.8         | 2.2         | 2.5         | 3.2         | 4            | 5            | 5.6          | 6.3          | 7            | 7.5          |
| Debit Aer (m³/h)               | 500/440/300 | 500/440/300 | 500/440/300 | 500/440/300 | 630/460/320  | 850/580/500  | 850/580/500  | 1100/850/650 | 1100/850/650 | 1200/850/650 |
| Putere absorbită (W)           | 20          | 20          | 20          | 20          | 25           | 35           | 35           | 50           | 50           | 65           |
| Curent nominal (A)             | 0.1         | 0.1         | 0.1         | 0.1         | 0.12         | 0.17         | 0.17         | 0.24         | 0.24         | 0.31         |
| Curent siguranță (A)           | 6           |             |             |             |              |              |              |              |              |              |
| Presiune sonoră (dB(A))        | 35/33/30    | 35/33/30    | 35/33/30    | 35/33/30    | 38/35/31     | 43/40/37     | 43/40/37     | 43/41/37     | 43/41/37     | 44/41/37     |
| Alimentare electrică (V/Ph/Hz) | 230V/1/50   |             |             |             |              |              |              |              |              |              |
| Agent frigorific               | R410A       |             |             |             |              |              |              |              |              |              |
| Diametru teava - lichid (mm)   | 6.35        | 6.35        | 6.35        | 6.35        | 6.35         | 6.35         | 6.35         | 9.52         | 9.52         | 9.52         |
| Diametru teava - gaz (mm)      | 9.52        | 9.52        | 9.52        | 9.52        | 12.7         | 12.7         | 12.7         | 15.9         | 15.9         | 15.9         |
| Diametru tub drenaj (mm)       | 20x1.5      | 20x1.5      | 20x1.5      | 20x1.5      | 20x1.5       | 20x1.5       | 20x1.5       | 30x1.5       | 20x1.5       | 30x1.5       |
| Dimensiuni unitate L×I×A (mm)  | 845×209×289 | 845×209×289 | 845×289×209 | 845×289×209 | 845×289×209  | 970×300×224  | 970×300×224  | 1078×325×246 | 1078×246×325 | 1078×325×246 |
| Dimensiuni ambalaj (mm)        | 973×278×364 | 973×278×364 | 973×258×370 | 973×258×370 | 1068×288×395 | 1068×288×395 | 1068×288×395 | 1131×398×328 | 1200×335×410 | 1131×398×328 |
| Greutate netă (kg)             | 10.5        | 10.5        | 10.5/12.5   | 10.5/12.5   | 10.5/12.5    | 12.5         | 12.5         | 16.0/19.0    | 16.0         | 16.0/19.0    |
| Greutate brută (kg)            | 12.5        | 12.5        | 12.5        | 12.5        | 12.5         | 15.5         | 15.5         | 19.0         | 19.0         | 19.0         |

De perete — seria CHV-5SW

3 modele: CHV-5SW80NK2 ... CHV-5SW100NK2

| Model                          | 5SW80NK2      | 5SW90NK2      | 5SW100NK2     |
|--------------------------------|---------------|---------------|---------------|
| Capacitate de răcire (kW)      | 8             | 9             | 9.5           |
| Capacitate de încălzire (kW)   | 9             | 10            | 10.5          |
| Debit Aer (m³/h)               | 1550/1050/800 | 1550/1050/800 | 1650/1100/900 |
| Putere absorbită (W)           | 80            | 80            | 100           |
| Curent nominal (A)             | 0.41          |               |               |
| Curent siguranță (A)           | 6             |               |               |
| Presiune sonoră (dB(A))        | 49/46/40      | 49/46/40      | 52/48/40      |
| Alimentare electrică (V/Ph/Hz) | 230V/1/50     |               |               |
| Agent frigorific               | R410A         |               |               |
| Diametru teava - lichid (mm)   | 9.52          |               |               |
| Diametru teava - gaz (mm)      | 15.9          |               |               |
| Diametru tub drenaj (mm)       | 20x1.5        |               |               |
| Dimensiuni unitate L×I×A (mm)  | 1350×258×326  |               |               |
| Dimensiuni ambalaj (mm)        | 1493×354×418  |               |               |
| Greutate netă (kg)             | 18.5          |               |               |
| Greutate brută (kg)            | 23.5          |               |               |

Consolă — seria CHV-5SK

5 modele: CHV-5SK22NK ... CHV-5SK50NK

| Model                          | 5SK22NK                                  | 5SK28NK     | 5SK36NK     | 5SK45NK     | 5SK50NK     |
|--------------------------------|------------------------------------------|-------------|-------------|-------------|-------------|
| Capacitate de răcire (kW)      | 2.2                                      | 2.8         | 3.6         | 4.5         | 5           |
| Capacitate de încălzire (kW)   | 2.5                                      | 3.2         | 4           | 5           | 5.5         |
| Debit Aer (m³/h)               | 400/320/270                              | 400/320/270 | 480/400/310 | 680/600/500 | 680/600/500 |
| Putere absorbită (W)           | 15                                       | 15          | 20          | 40          | 40          |
| Curent nominal (A)             | 0.17                                     | 0.17        | 0.25        | 0.4         | 0.4         |
| Curent siguranță (A)           | 6                                        |             |             |             |             |
| Presiune sonoră (dB(A))        | 38/33/27                                 | 38/33/27    | 40/37/32    | 46/43/39    | 46/43/39    |
| Alimentare electrică (V/Ph/Hz) | 220-240V/1/50Hz                          |             |             |             |             |
| Agent frigorific               | R410A                                    |             |             |             |             |
| Diametru teava - lichid (mm)   | 6.35                                     |             |             |             |             |
| Diametru teava - gaz (mm)      | 9.52                                     | 9.52        | 9.52        | 12.7        | 12.7        |
| Diametru tub drenaj (mm)       | 17.2x1.0 (Ø17.2 exterior, perete 1.0 mm) |             |             |             |             |
| Dimensiuni unitate L×I×A (mm)  | 700×215×600                              |             |             |             |             |
| Dimensiuni ambalaj (mm)        | 780×682×285                              |             |             |             |             |
| Greutate netă (kg)             | 16                                       |             |             |             |             |
| Greutate brută (kg)            | 19                                       |             |             |             |             |

Consolă de pardoseală — seria CHV-5SFC

7 modele: CHV-5SFC22NK ... CHV-5SFC71NK

| Model                          | 5SFC22NK                    | 5SFC28NK    | 5SFC36NK    | 5SFC45NK     | 5SFC56NK     | 5SFC63NK     | 5SFC71NK     |
|--------------------------------|-----------------------------|-------------|-------------|--------------|--------------|--------------|--------------|
| Capacitate de răcire (kW)      | 2.2                         | 2.8         | 3.6         | 4.5          | 5.6          | 6.3          | 7.1          |
| Capacitate de încălzire (kW)   | 2.5                         | 3.2         | 4.0         | 5.0          | 6.3          | 7.1          | 8.0          |
| Debit Aer (m³/h)               | 450/350/250                 | 450/350/250 | 550/450/350 | 650/500/400  | 900/750/600  | 900/750/600  | 1100/900/700 |
| Putere absorbită (W)           | 35                          | 35          | 43          | 45           | 80           | 80           | 90           |
| Curent nominal (A)             | 0.2                         | 0.2         | 0.3         | 0.3          | 0.43         | 0.43         | 0.48         |
| Curent siguranță (A)           | 6                           |             |             |              |              |              |              |
| Presiune sonoră (dB(A))        | 30/28/25                    | 30/28/25    | 33/31/28    | 33/31/28     | 35/33/30     | 35/33/30     | 37/35/33     |
| Alimentare electrică (V/Ph/Hz) | 220~240 V / 1F / 50 Hz      |             |             |              |              |              |              |
| Agent frigorific               | R410A                       |             |             |              |              |              |              |
| Diametru teava - lichid (mm)   | 6.35                        | 6.35        | 6.35        | 6.35         | 9.52         | 9.52         | 9.52         |
| Diametru teava - gaz (mm)      | 9.52                        | 9.52        | 12.7        | 12.7         | 15.9         | 15.9         | 15.9         |
| Diametru tub drenaj (mm)       | 28x1 (OD 28 mm, perete 1.0) | 28x1        | 28x1        | 28x1         | 25x2.5       | 25x2.5       | 25x2.5       |
| Dimensiuni unitate L×I×A (mm)  | 700×615×200                 | 700×615×200 | 700×615×200 | 900×615×200  | 1100×615×200 | 1100×615×200 | 1100×615×200 |
| Dimensiuni ambalaj (mm)        | 890×290×740                 | 890×290×740 | 890×290×740 | 1120×290×740 | 1320×290×740 | 1320×290×740 | 1320×290×740 |
| Greutate netă (kg)             | 23                          | 23          | 23          | 27           | 32           | 32           | 32           |
| Greutate brută (kg)            | 30                          | 30          | 30          | 36           | 41           | 41           | 41           |